

CLAIM AMENDMENTS:

1 - 19 cancelled

20. (currently amended) The method of ~~claim 18~~claim 36, wherein the expected future course of travel is determined using information concerning a steering angle of the vehicle and a fictitious camera position is illustrated in a lower portion of the image.
21. (currently amended) The method of ~~claim 19~~claim 36, wherein the ~~graphical object which is faded into the image of the camera device to illustrate the course of travel comprises a symbol indicating an end of travel motion, the symbol being~~is a limiting line, limiting means symbolically presented on the course of travel, a barrier, a gate, or a fence disposed approximately at a level of the determined position of the obstacle in the image.
22. (currently amended) The method of ~~claim 19~~claim 36, wherein the first graphical object illustrating the course of travel is imaged only to approximately a level of the determined position of the obstacle in the image, but not for larger distances from the vehicle or the camera device.
23. (currently amended) The method of ~~claim 19~~claim 36, wherein for large separations from the vehicle beyond an approximate location of the determined position of the obstacle in the image, the first graphical object in the form of the course of travel is only schematically indicated or is indicated using broken lines.

24. (currently amended) The method of ~~claim 18~~claim 36, wherein, as viewed by the camera device, at least one region of the surroundings of the vehicle is determined in which the obstacle is located and at least one graphical object is faded into the image of the camera device to optically emphasize a correlation between the obstacle and the at least one region and/or a position of the obstacle within this region.
25. (previously presented) The method of claim 24, wherein a bar or a bar which extends in a vertical direction from a lower edge of the image is faded into the image as the graphical object to indicate the position of the obstacle relative to the position of the vehicle or the camera device, wherein a horizontal position of the bar in the image represents the region of the surrounding and/or a height or length of the bar in a vertical direction represents the determined distance between the obstacle and the vehicle.
26. (previously presented) The method of claim 25, wherein an outline of the bar is adjusted to the representation of the determined course of travel and is illustrated in a correspondingly bent and/or distorted fashion.
27. (currently amended) The method of ~~claim 18~~claim 36, wherein a graphical object is faded into the image at the position of the obstacle in the image or at a position of a side of the obstacle facing or closest to the camera device, wherein the obstacle is at least partially covered.
28. (previously presented) The method of claim 27, wherein the outline of the graphical object has a basic geometric form, is rectangular, oval, triangular or has a form of a determined outline of the obstacle.

29. (currently amended) The method of ~~claim 19~~claim 36, wherein the first graphical object is semi-transparent or represented only as an outline.
30. (currently amended) The method of ~~claim 19~~claim 36, wherein the first graphical object is represented as a colored surface, wherein a color can optionally be varied in accordance with the determined distance between the obstacle and the vehicle or the camera device.
31. (currently amended) The method of ~~claim 18~~claim 36, wherein the image of the camera device is manipulated, brightened, or colored in a region of the determined position of the obstacle, wherein the manipulation depends on a magnitude of the determined distance between the obstacle and the vehicle, varies in time and/or flashes.
32. (currently amended) A computer ~~program~~readable storage medium comprising a program code for a vehicle warning device, wherein the program code is designed to perform the method of ~~claim 18~~claim 36.
33. (cancelled)
34. (cancelled)
35. (currently amended) The ~~warning device of claim 34~~device of claim 37, wherein the means for image processing device is designed to process the image of the camera device while taking into consideration vehicle parameters or a vehicle steering angle.

36. (new) A method for graphically processing an image, provided by a camera device, of surroundings of a vehicle or in a direction of travel of the vehicle for presentation to an observer or to a driver of the vehicle, the method comprising the steps of:

- a) detecting an obstacle in the surroundings of the vehicle;
- b) determining a position of the obstacle relative to a position of the vehicle;
- c) determining a position of the obstacle relative to the surroundings;
- d) determining a position of the obstacle in the image provided by the camera device;
- e) processing the image thereby taking into consideration the determined position of the obstacle in the image;
- f) displaying the processed image, wherein the position of the obstacle in the surroundings is determined using the known distance between the obstacle and the vehicle or the camera device and the position of the obstacle in the image or of a side of the obstacle facing or closest to the camera device represents the determined actual distance between the obstacle and the camera device;
- g) fading a first graphical object into the displayed image, the first graphical object illustrating an expected future course of travel of the vehicle; and
- h) fading a second graphical object into the displayed image, the second graphical object comprising a symbol indicating an end of travel motion and disposed approximately at a level of the determined position of the obstacle in the image, wherein the end of travel motion symbol extends substantially transverse to

the illustrated expected future course of travel at a location thereof directly before the displayed position of the obstacle.

37. (new) A device for graphically processing an image, provided by a camera device, of surroundings of a vehicle or in a direction of travel of the vehicle for presentation to an observer or to a driver of the vehicle, the device comprising:

- means for detecting an obstacle in the surroundings of the vehicle;
- means for determining a position of the obstacle relative to a position of the vehicle;
- means for determining a position of the obstacle relative to the surroundings;
- means for determining a position of the obstacle in the image provided by the camera device;
- means for processing the image thereby taking into consideration the determined position of the obstacle in the image;
- means for displaying the processed image, wherein the position of the obstacle in the surroundings is determined using the known distance between the obstacle and the vehicle or the camera device and the position of the obstacle in the image or of a side of the obstacle facing or closest to the camera device represents the determined actual distance between the obstacle and the camera device;
- means for fading a first graphical object into the displayed image, the first graphical object illustrating an expected future course of travel of the vehicle; and
- means for fading a second graphical object into the displayed image, the second graphical object comprising a symbol indicating

an end of travel motion and disposed approximately at a level of the determined position of the obstacle in the image, wherein the end of travel motion symbol extends substantially transverse to the illustrated expected future course of travel at a location thereof directly before the displayed position of the obstacle.